

## 

(43) International Publication Date 25 May 2001 (25.05.2001)

## (10) International Publication Number WO 01/37013 A1

(51) International Patent Classification7:

G02B 6/287

(21) International Application Number: PCT/CA00/01314

(22) International Filing Date:

6 November 2000 (06.11.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2,289,962

17 November 1999 (17.11.1999)

(71) Applicant (for all designated States except US): ITF OP-TICAL TECHNOLOGIES INC.-TECHNOLOGIES OPTIQ UES ITF INC. [CA/CA]; 45 Montpellier Blvd., Ville St-Laurent, Quebec H4N 2G3 (CA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): GONTHIER, François [CA/CA]; 274 Trenton, Ville Mont-Royal, Quebec H3P 1Z7 (CA).

(74) Agent: PRIMAK, George, J.; 13480 Huntington, Pierrefonds, Quebec H8Z 1G2 (CA).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

## Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FABRICATION OF MULTIPLEXING AND DEMULTIPLEXING SINGLE-MODE FIBER OPTIC COUPLERS



(57) Abstract: Multiplexing and demultiplexing single-mode fiber optic couplers are fabricated by aligning two single-mode fibers which have been stripped of their protective plastic jackets and cleaned so that they are held in parallel contact with each other, and then fusing these fibers to achieve a desired fusion profile and elongating the fused fibers to achieve a match point between the wavelength period and the polarization phase. The elongation process is interrupted and resumed as required to obtain a precise match point required to produce the desired multiplexing or demultiplexing coupler.

Ţ T T j